

CERTIFICATE

Certificate registration number: G3.1612.113.1.A2

Certificate holder: Semtech Corporation

Platform designation: ENIGMA, Hardware version EV8000, Firmware version 4.0

Certification date: December 9th, 2016

This certificate indicates the above mentioned platform successfully completed certification testing with regards to the reference specification ITU G.9903 (02-2014) plus the changes listed in the annex to this certificate. The optional feature coherent mode of the G3-PLC protocol is also covered by this certification.

The certificate applies to certification profile Metering Cenelec A and the device was configured as a PAN-Coordinator.

Test cases have been performed as described in the test report referred to below. This certificate is granted on account of tests conducted by Laboratoire des Applications Numériques (LAN) in Tauxigny, France in October - November 2016. The results and remarks can be found in the complete test report.

Applied tests	Performed by	Document evidence
Conformance and interoperability testing according to the test specification referenced by the test report	Laboratoire des Applications Numériques (LAN)	LAN16AF078

The device tested is a G3-PLC platform: a solution providing an implementation of the G3-PLC specification. This certificate is valid from December 9th, 2016.

The certificate is only applicable to the platform described above and permits the use of the G3-PLC™ logo as laid down in the G3-PLC logo license agreement.

This certificate does not imply assessment of the production. This certificate shall not be defined, or used as a guarantee covering quality of a product which includes G3-PLC. The liability of the Alliance and the test laboratory or any of her representatives is excluded for any damages or losses of the certified company.

Paris, December 9th, 2016

For the G3-PLC Alliance:

Bernard Lassus Chairman Madeleine Francillard
Chair Certification Program





Annex 1: Reference Version for Certification

The reference version for this certificate is published in 'Narrowband OFDM PLC specifications for G3-PLC network, April 2015'.

The reference version for this certification is:

ITU-T G.9903 (02-2014)

- + CCTT #24-25-30: Implementation of MAC security (anti-replay) solution F1
- + CCTT #61: ADPM-Buffer behavior clarification
- + CCTT #143: AC Phase Detection v2
- + CCTT #144: Hop Limit usage during route repair v3
- + CCTT #145: Value of RCCoord when the node is at adpMaxHops hops from the coordinator
- + CCTT #146: Pilot tone generation
- + CCTT #147: Link-cost computation for Path discovery v2
- + CCTT #148: Path discovery frame routing v3
- + CCTT #152: Scrambler reset
- + CCTT #154: Clarification of PANCount and PANDescriptor
- + CCTT #156: Clarification of ADPM-NETWORK-STATUS.indication
- + CCTT #157: Interleaver Equation v2
- + CCTT #158: Unicast Routing Process
- + CCTT #159: Correct the windowing function description
- + CCTT #160: Clarify 16QAM quantisation and optionality
- + CCTT #161: Correct aMaxFrameSize and aMinFrameSize for FCC/ARIB bandplans
- + CCTT #162: Interleaver co-prime number clarification v2
- + CCTT #163: CRC5 and CRC8 packing order
- + CCTT #164: Route Repair v2
- + CCTT #165: Clarification Neighbour Table v2
- + CCTT #167: HOP COUNT metric identifier v2
- + CCTT #169: Clarification on PLME_GET v4
- + CCTT #170: Clarification to Frame Counter Handling Mechanism v2
- + CCTT #172: Windowing in coherent mode
- + CCTT #173: Clarification of LOADng mechanism used to detect bidirectional links
- + CCTT #174: Avoiding duplicated MAC packets
- + CCTT #175: LOADng subsequent RREP generation
- + CCTT #176: Link cost function of LQI v3
- + CCTT #177: Broadcast routing filtering frames on the source
- + CCTT #178: Coexistence of G3-PLC with other PLC technologies v3
- + CCTT #179: RREP Filtering v3
- + CCTT #181: Route Repair v2

II he

Certificate registration number: G3.1612.113.1.A2 Page 2 of 5



Annex 2: Protocol Implementation Conformance Statement (PICS)

Feature implementation statement

Name	Value	Description	
BAND_PLAN	CENELEC A	Indicate the band-plan supported by the device.	
FEATURE_PAN_COORDINATOR	TRUE	Indicate if the device is a PAN-Coordinator (true) or a normal device (false)	
FEATURE_COHERENT_MODULAT ION	TRUE	Indicate if coherent modulation is supported	
FEATURE_EAP_SERVER TF	T0.115	Indicate if an EAP-PASK server is implemented by the DUT.	
	TRUE	Apply only if FEATURE_PAN_COORDINATOR = true	
FEATURE_D8PSK_MODULATION	TRUE	True / False	
FEATURE_ROUTING	TRUE	Indicate if the routing is implemented by the IUT	
FEATURE_SECURITY	F1	Indicate the security implemented by the device. Possible values are: F1, F2.	
FEATURE_ACTIVE_SCAN	TRUE	Indicate if the active scan process is done by the IUT after power-up	
FEATURE_PREAMBLE_COEXISTE NCE_MECHANISM	FALSE	Indicate if the preamble-based coexistence mechanism is used by the IUT.	







Annex 3: Copy of test report cover sheet









ENIGMA HW:EV8000 FW: 4.0

LAN16AF078 Ed.00 November 29, 2016 Page 1/25



G3-PLC Platform Certification Test Report

Vendor Name

SEMTECH

Model Name

ENIGMA

Serial N° HW version 32640 EV8000

FW version

Test Report #

-TR_LAN16AF078 Ed.00 November 29, 2016

Date

CONF Tests Specification **CONF Tests Suite IOT Tests Specification IOT Tests Suite**

version 0.49, 01/09/2015 version 2.1. 10/2015 version 0.7. 21/04/2015 version 2.1. 10/2015

version 1.7 Test Tool version 1.09 Tester Modem

version 1.7. 30/05/2016 Certification Test Procedures

Certification Profile

Role

A (CENELEC A) **PAN Coordinator**

Overall Verdict PASS



Initiation

Description of modification

Ed.

Omar DIOUF

November 29, 2016

Creation

Name

Realised by Omar DIOUF

Checked by Vincent BUCHOUX November 29, 2016

Approved by Thierry DOLIGEZ November 29, 2016

Sign

Date



Certificate registration number: G3.1612.113.1.A2

Page 4 of 5



Annex 4: Additional details of the certified platform

Platform model name:	ENIGMA
Platform hardware version:	EV8000
Platform firmware version:	4.0
Exact part number of all the chips running G3-PLC stack in the certified platform:	EV8000ILPT
What each part number runs: lower MAC (incl. CSMA/CA) or PHY or other parts of the stack:	PHY+MAC+6LowPAN
Hardware version of this chip:	EV8000
Software version running on this chip:	4.0
Internal CPU frequency:	240 MHz

