



G3-PLC 500 kHz for Smart Metering

Dr. Michael Koch

Vice President Strategic Positioning

devolo
The Network Innovation

From the startup to the worldwide market leader in powerline solutions


devolo

devolo AG, Germany – subsidiaries

- devolo Asia Consulting Ltd.
- devolo Austria GmbH
- devolo Benelux bvba
- devolo France SARL
- devolo Schweiz GmbH
- devolo Spain SL
- devolo UK Ltd.

Further focused sales areas

- Italy, Portugal, Poland, Greece and Scandinavia (SE, NO, FI, DK, IS)
- Others currently under development



Three business units for the future

devolo

2013

2014

2015

Smart Grid

B2B

Home Control

B2C / B2B


Home Networking

B2C / B2B

Smart Metering Szenario


Typical application of the Access PLC for the Smart Grid Scenarios

devolo




Comparison of PLC Technologies


- + already available as PLC EMC standard: EN 50065
- + separate frequency band for energy supply company and private use
- low data rates
 - small frequency spectrum for PLC transmission
 - poor transmission channels as general EMC filtering is only above 150 kHz
- interaction with other devices, such as e.g. inverters and capacitive switches



- + high data rates
 - range ideal for in-house transmission, insufficient in the access area
 - the need for repeaters harms business plans
- devolo's concept for in-house PLC



- + high coverage and long range: longest transmission distance 1.7 km (measured in field tests; limited by infrastructure)
 - + significantly higher data rate compared to CENELEC band, but lower than in the band above medium wave radio broadcast
- devolo's concept for IP-based communication in PLC Access Networks/Smart Grid applications



G3-PLC road to an international standard



2008
2009

- May 2008: International contest for the design of G3-PLC (Launched by ERDF)
- Oct 2009: G3-PLC first field tests on 5 nodes – Presentation of the results at Metering Barcelona

2010
2011

- Sep 2011: Creation of the G3-PLC Alliance with 12 founding members
- Dec 2011: G3-PLC ITU standard – G9955 and G9956
- Successful interoperability tests

2012
2013

- G3-PLC ITU T standard – New version G 9903 (Cenelec A, FCC, ARIB)
- Clarifications and enhancement brought by IOT
- Development of the certification processes


2014

- Feb 2014: First interim certificates, Arib band
- Apr 2014: G3-PLC ITU Standard (Cenelec A, FCC, ARIB)
- Aug 2014: Official certification

IP-Access Powerline for Smart Grids

Field trials by Vattenfall and devolo in Hamburg and Berlin

devolo



- IP-based PLC in real time
- High- speed with long distances by usage 150- 500 kHz
- Fast, reliable performance

Field Trial in Hamburg Bramfeld


devolo

GOALS OF TEST

- Determination of round trip delay time
- Determination of bandwidth in the physical layer
- Calculation of bandwidth in the application layer
- Accessibility of the nodes
- Channel measurement
- Analysis of the lead time for parametrizing and firmware upload to the meters


DESCRIPTION OF ENVIRONMENT

- Typical environment of urban grid
- High concentrated grid
- Distance between the nodes: min. 200 m
- Installation of one access point in a substation
- Installation of 22 nodes at costumers' premises
- Test only with synthetic data



Performance Test Results

devolo



PLEASE NOTE:

Achieved data rates are on application layer - physical layer data rates are nominally much higher.

G3-PLC based Fieldtrials with Vattenfall

Berlin Trials

devolo

- Aim

Evaluation of data rates, distances and channel characterization of G3-PLC 500k in areas where CENELEC-PLC failed due to difficult power grid conditions.



- Locations

- Berlin, Märkisches Viertel: Extensive domestic complex.
- Berlin, Hohenschönhausen: Multi dwelling unit
- Berlin, Kaulsdorf: Low voltage overhead wire.



Märkisches Viertel



Hohenschönhausen



Kaulsdorf

- Results

- Stable communication connections
- Data rates of up to 70 kBit/s payload UDP
- The achieved distances were by far longer than expected.

Next step: >1000 industrialized products will be tested in the biggest two cities of Germany (Berlin, Hamburg)!

G3-PLC based Fieldtrials with Vattenfall – Berlin Results

Flat buildings with 20 floors



		Meter 1	Meter 2	Meter 3	Meter 4	Meter 5	Meter 6
Throughput [kBit/s]	max:	84	83	82	79	81	82
	avg:	79	81	76	73	53	77
	min:	60	74	56	45	22	59
Round Trip Delay [ms]	max:	513	469	474	503	1267	574
	avg:	433	426	437	448	650	441
	min:	418	417	427	426	490	419




System requirements of the Commission

Recommendation of 9.3.2012, C(2012) 1342 on preparations for the roll out of smart metering systems

- (10) ***Data protection and information security features should be built into smart metering systems before they are rolled out and used extensively.*** Such features can effectively improve consumers' control over the processing of personal data.
- (11) ... to stimulate and support introduction of the '***security and data protection by design***' principle at an early stage in the development of smart grids, particularly ***for the roll-out of smart metering systems.***
- (15) ***An assessment of the data protection impact carried out by the operator*** and stakeholders prior to the roll-out of smart metering systems will provide the information necessary in order to take appropriate protective measures. Such measures should ***be monitored and reviewed throughout the lifetime of the smart meter.***

→ German concept: Introduction of a Smart Meter Gateway (SMGW)

Overview of Smart Metering System in Germany



Security and Privacy are ensured by the Smart Meter Gateway

- Protection of confidentiality, authentication, integrity of data
- End-to-End Security
- Information flow control

→ Requirement for higher data rates than without security/protection

- devolo's access technology approach based on G3-PLC 150-500 kHz has a very high potential as communication infrastructure for smart metering systems and other Smart Grid applications
 - Support of IP-traffic
 - Data rates observed during the field trials are typically higher than 50 kBit/s (payload TCP)
 - This is above present estimations for data rates requirements for metering systems and Smart Grid application.
 - With it's coverage and the observed distances, repeaters are generally not necessary.
 - Data transmission is robust against interferences on the power grid.
 - No interferences have been observed against other systems.
- System requirements on security and data protections increase data rates requirements.
 - CENELEC PLC systems cannot meet these requirements.

Next step: >1000 industrialized products will be tested in the biggest two cities of Germany (Berlin, Hamburg)!

devolo G3-PLC Modem 500k

Reliable data transmission in Smart Grids

devolo

G3-Powerline technology for efficient communication on smart grids.

G3-PLC uses your existing power grid to transmit data from smart meters, infeed renewable energy sources and grid status measurement.

Powerline is the essential technology to build up a smart grid in your municipality.



„We have extensively tested devolo’s G3-PLC Modem 500k prototype. Our expectations have been greatly surpassed. That’s why we run a large field test with devolo’s serial product.“

Jan-Philipp Blenk

Project Manager Vattenfall Europe Metering GmbH



**Thank you very much
for your attention.**

Dr. Michael Koch
Phone +49 241 18279 160
Mobile +49 151 544 31627
Michael.Koch@devolo.de

devolo
The Network Innovation